



अखिल भारतीय आयुर्विज्ञान संस्थान , बिलासपुर
हिमाचल प्रदेश -१७४००१
All India Institute of Medical Sciences, Bilaspur
Himachal Pradesh-174001
<https://aiimsbilaspur.edu.in>
engineering@aiimsbilaspur.edu.in



AIIMS-BLS-H-24/EE-0002/2023-24

Dated: 12/03/2024

NOTICE INVITING QUOTATION

Sealed item rate quotations as per schedule attached are hereby invited by the undersigned on behalf of the Executive Director, AIIMS Bilaspur (HP) from registered contractors so as to reach in this office on or before **20/03/2024 up to 03:00 PM** and shall be opened on the same day at **03:30 PM** in the O/o Executive Engineer, AIIMS Bilaspur (HP) in the presence of intending contractors or their authorized representatives.

Name of work: Renovating the CGHS & IPD registration space, AIIMS Bilaspur H.P
Estimated Cost: Rs 86.08 Thousand

-----As Per Schedule Attached-----

Terms & Conditions: -

1. The work will be carried out as per CPWD General Specifications for Civil Works amended up to date & as per the instructions of the Engineer-in-charge.
2. The work is to be completed within 15 days from issue of work order.
3. Any damages done during execution of the work/repairs are to be made good by the agency and nothing extra will be paid separately for the same.
4. The Prices quoted should be inclusive of all taxes including GST and nothing extra is to be paid.
5. Agency shall abide by labour rules.
6. All the applicable taxes shall be deducted from the bill.
7. Compensation of delay work will be @0.5% per week.
8. GST Registration Certificate should also be attached with NIQ.
9. Certificate of enlistment with Central/State Govt. Organization/Central Autonomous body/Central Public Sector Undertaking should also be attached with NIQ.
10. All material to be used on the work will have to be got approved from the Engineer-in-charge.

Sd/-
Executive Engineer

Copy To:-

- (i) Institute Website
- (ii) Notice Board

Sd/-
Executive Engineer

Schedule Of Quantity

Renovating the CGHS & IPD registration space, AIIMS Bilaspur H.P

S.No	Description of work	Qty	Unit	Rate (in Rs)		Amount (In Rs)
				(In Figures)	(In Words)	
1	<p>Providing and fixing partition upto ceiling height consisting of G.I. frame and required board, including providing and fixing of frame work made of special section power pressed/ roll form G.I. sheet with zinc coating of 120 gms/sqm(both side inclusive), consisting of floor and ceiling channel 50mm wide having equal flanges of 32 mm and 0.50 mm thick, fixed to the floor and ceiling at the spacing of 610 mm centre to centre with dash fastener of 12.5 mm dia meter 50 mm length or suitable anchor fastener or metal screws with nylon plugs and the studs 48 mm wide having one flange of 34 mm and other flange 36 mm and 0.50 mm thick fixed vertically within flanges of floor and ceiling channel and placed at a spacing of 610 mm centre to centre by 6 mm dia bolts and nuts, including fixing of studs along both ends of partition fixed flush to wall with suitable anchor fastener or metal screws with nylon plugs at spacing of 450 mm centre to centre, and fixing of boards to both side of frame work by 25 mm long dry wall screws on studs, floor and ceiling channels at the spacing of 300 mm centre to centre. The boards are to be fixed to the frame work with joints staggered to avoid through cracks, M.S. fixing channel of 99 mm width (0.9 mm thick having two flanges of 9.5 mm each) to be provided at the horizontal joints of two boards, fixed to the studs using metal to metal flat head screws, including jointing and finishing to a flush finish with recommended jointing compound, jointing tape, angle beads at corners (25 mm x 25 mm x 0.5 mm), joint finisher and two coats of primer suitable for board as per manufacture's specification and direction of engineer in charge all complete.</p>					
	<p>66mm overall thickness Partition with 8mm thick double skin Calcium Silicate Board made with Calcareous & Siliceous materials reinforced with cellulose fiber manufactured through autoclaving process with Compressive Strength 225 kg/sq.cm, Bending Strength 100 kg./ sq.cm</p>	25	sqm			

2	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	50	sqm			
3	Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications :					
	Two or more coats applied on walls @ 1.25 ltr/10 sqm. over and including one coat of Special primer applied @ 0.75 ltr / 10sqm	50	sqm			