



अखिल भारतीय आयुर्विज्ञान संस्थान , बिलासपुर
हिमाचल प्रदेश -१७४००१
All India Institute of Medical Sciences, Bilaspur
Himachal Pradesh-174001
<https://aiimsbilaspur.edu.in>
engineering@aiimsbilaspur.edu.in



AIIMS-BLS-H-24/EE-0003/2023-24

Dated: 12/03/2024

NOTICE INVITING QUOTATION

Sealed item rate quotations as per schedule attached are hereby invited by the undersigned on behalf of the Executive Director, AIIMS Bilaspur (HP) from registered contractors so as to reach in this office on or before **20/03/2024 up to 03:00 PM** and shall be opened on the same day at **03:30 PM** in the O/o Executive Engineer, AIIMS Bilaspur (HP) in the presence of intending contractors or their authorized representatives.

Name of work: Partition work in Nephro Ward area for setting up of three bed Renal Transplant ICU.

Estimated Cost: Rs 1.16 Lac

-----As Per Schedule Attached-----

Terms & Conditions: -

1. The work will be carried out as per CPWD General Specifications for Civil Works amended up to date & as per the instructions of the Engineer-in-charge.
2. The work is to be completed within 15 days from issue of work order.
3. Any damages done during execution of the work/repairs are to be made good by the agency and nothing extra will be paid separately for the same.
4. The Prices quoted should be inclusive of all taxes including GST and nothing extra is to be paid.
5. Agency shall abide by labour rules.
6. All the applicable taxes shall be deducted from the bill.
7. Compensation of delay work will be @0.5% per week.
8. GST Registration Certificate should also be attached with NIQ.
9. Certificate of enlistment with Central/State Govt. Organization/Central Autonomous body/Central Public Sector Undertaking should also be attached with NIQ.
10. All material to be used on the work will have to be got approved from the Engineer-in-charge.

Sd/-
Executive Engineer

Copy To:-

- (i) Institute Website
- (ii) Notice Board

Sd/-
Executive Engineer

Schedule Of Quantity

Renovating the Nephro Ward area, AIIMS Bilaspur H.P

S.No	Description of work	Qty	Unit	Rate (in Rs)		Amount (In Rs)
				(In Figures)	(In Words)	
1	<p>Providing and fixing partition upto ceiling height consisting of G.I. frame and required board, including providing and fixing of frame work made of special section power pressed/ roll form G.I. sheet with zinc coating of 120 gms/sqm(both side inclusive), consisting of floor and ceiling channel 50mm wide having equal flanges of 32 mm and 0.50 mm thick, fixed to the floor and ceiling at the spacing of 610 mm centre to centre with dash fastener of 12.5 mm dia meter 50 mm length or suitable anchor fastener or metal screws with nylon plugs and the studs 48 mm wide having one flange of 34 mm and other flange 36 mm and 0.50 mm thick fixed vertically within flanges of floor and ceiling channel and placed at a spacing of 610 mm centre to centre by 6 mm dia bolts and nuts, including fixing of studs along both ends of partition fixed flush to wall with suitable anchor fastener or metal screws with nylon plugs at spacing of 450 mm centre to centre, and fixing of boards to both side of frame work by 25 mm long dry wall screws on studs, floor and ceiling channels at the spacing of 300 mm centre to centre. The boards are to be fixed to the frame work with joints staggered to avoid through cracks, M.S. fixing channel of 99 mm width (0.9 mm thick having two flanges of 9.5 mm each) to be provided at the horizontal joints of two boards, fixed to the studs using metal to metal flat head screws, including jointing and finishing to a flush finish with recommended jointing compound, jointing tape, angle beads at corners (25 mm x 25 mm x 0.5 mm), joint finisher and two coats of primer suitable for board as per manufacture's specification and direction of engineer in charge all complete.</p>					
	<p>66mm overall thickness Partition with 8mm thick double skin Calcium Silicate Board made with Calcareous & Siliceous materials reinforced with cellulose fiber manufactured through autoclaving process with Compressive Strength 225 kg/sq.cm, Bending Strength 100 kg./ sq.cm</p>	12	sqm			

2	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	24	sqm			
3	Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications :					
	Two or more coats applied on walls @ 1.25 ltr/10 sqm. over and including one coat of Special primer applied @ 0.75 ltr / 10sqm	24	sqm			
4	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :					
	For fixed portion					
	Powder coated aluminium (minimum thickness of powder coating 50 micron)	18	sqm			
5	Providing and fixing double action hydraulic floor spring of approved brand and manufacture conforming to IS : 6315, having brand logo embossed on the body / plate with double spring mechanism and door weight upto 125 kg., for doors, including cost of cutting floors ,embedding in floors as required and making good the same matching to the existing floor finishing and cover plates with brass pivot and single piece M.S. sheet outer box with slide plate etc. complete as per the direction of Engineer-in-charge.					
	With brass cover plate minimum 1.25 mm thickness.	4	no			
6	Providing and fixing 12mm thick prelaminated particle board flat pressed three layer or graded wood particle board					

	conforming to IS:12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.					
	Pre-laminated particle board with decorative lamination on both sides.	6	sqm			
7	Providing and fixing ISI marked oxidised M.S. handles conforming to IS:4992 with necessary screws etc. complete (Copper oxidised as per IS 1378)					
	125 mm	1	no			
8	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item):					
	With float glass panes of 8 mm thickness (weight not less than 20 kg/sqm)	4	sqm			
9	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately).					
	Powder coated aluminium (minimum thickness of powder coating 50 micron)	45	kg			